




STARK ()

WL

Features

- > SAE, CA T13, R65, R10, NAFA, J1119 and KKK certified
- > Multi-functional with warning light and worklight
- > Worklight offers homogeneous illumination right around the nearby rescue area
- > Available in single, split, dual and triple colors
- > Rugged weather-resistant enclosure
- > Synchronize with other Stark O series
- > Aluminum die-casting base provides excellent heat dissipation
- > IP69K
- > 5 year warranty



Single Color

Item	Color	Signal Light	Voltage	Max Power	Lens	LED	Flash Patterns	Operating Temperature	Mounting
140201	•	×	10-33VDC	40W	TIR +Reflex	6pcs 3W	96	-30 to 70°C	Surface Mount
						12pcs 1.5W			

Dual Color

	ltem	Color	Signal Light	Voltage	Max Power	Lens	LED	Flash Patterns	Operating Temperature	Mounting
1	140202	•	×	10-33VDC	40W	TIR +Reflex	12pcs 3W	- 96	-30 to 70°C	Surface Mount
	140202						12pcs 1.5W			

Triple Color

ltem	Color	Signal Light	Voltage	Max Power	Lens	LED	Flash Patterns	Operating Temperature	Mounting	
140203	•	×	10-33VDC	40W	TIR +Reflex	18pcs 3W	- 96	-30 to 70°C	Surface Mount	
						12pcs 1.5W				

911 Signal Technology Inc.

China Office Tel: +86-574-89017911 Fax: +86-574-82822560 Email: sales@911signal.com France Office Tel: +33(0)659163209 Email: euoffice@911signalgroup.com www.911signal.com

